



DRILL/AUGER/CULTIVATOR



EDR-260
ENGINE DRILL

2 year Commercial Warranty
5 year Consumer Warranty



Featuring compact power for drilling holes for pest control or lineman applications.

- All-position diaphragm carburetor, with purge pump, allows operation at any angle
- Heavy-duty gear reduction converts engine power into tough drilling torque
- Reversible function
- Heavy-duty keyed chuck holds up to 1/2 in. drill shank

Engine (cc)	25.4
Weight (lbs.)	11.4
Fuel Capacity (fl. oz.)	19.6
RPM	0-650 Forward/Reverse
Torque (lbs. ft.)	12
Gear Reduction Ratio	17.1:1
Chuck dia. (in.)	1/2 Std.



EA-410
EARTH/ICE AUGER

2 year Commercial Warranty
5 year Consumer Warranty



A powerful tool for digging fence post holes, planting bulbs, or trees and ice fishing.

- Designed for a wide variety of auger diameters and lengths (sold separately see page 62)
- Heavy-duty handle and frame assembly reduces vibration for greater operator comfort
- Designed for either 1- or 2-person operation
- Drills through earth, snow and ice for year-round use

Engine (cc)	42.7
Weight (lbs.)	21.6
Fuel Capacity (fl. oz.)	33.8
RPM	348
Torque at auger (lbs. ft.)	48.9
Gear Reduction Ratio	30.2:1



TC-210
TILLER/CULTIVATOR

2 year Commercial Warranty
5 year Consumer Warranty



Boasting tremendous performance from a compact package for a variety of garden tilling tasks.

- Four, 10-tooth reversible, hardened-steel tines feature a lifetime warranty and provide smooth tilling action for up to 9 in. wide furrows
- Worm gear-type transmission (42:1 reduction) provides incredible digging torque with dirt-churning tine rpm
- Kickstand for easy storage
- Water resistant stop switch and throttle control located at operator's fingertips

Engine (cc)	21.2
Weight (lbs.)	21.3
Fuel Capacity (fl. oz.)	16.9
Furrow Width (in.)	9
Number of Tines	4



TILLER/AUGER ACCESSORIES

Tiller/Cultivator Kickstand Replacement

• TC-210

Part#: 99988800900



Earth Augers

All ECHO augers have a 7/8 in. diameter shaft opening. The 6 in., 8 in. and 10 in. augers feature a flex coil design to absorb ground shock while slowing impact between blade and rock for better handling and operation.

Diameter (in.)	Length (in.)	Weight (lbs.)	Part #
2	36	5.8	99944900150
3	36	6.5	99944900160
4	36	7.5	99944900170
6	34	12	99944900180
8	34	15	99944900190
10	34	18	99944900200

Dual-Blade Ice Augers

ECHO ice augers feature a centering ring to re-drill old holes. Unique coil technology slows the impact between blade, ice, or other debris.

Diameter (in.)	Length (in.)	Part #
8	40	99944900280
10	40	99944900290

SPECIFICATIONS

Model	Engine Disp. (cc)	Gear Reduction Ratio	Drill Speed (RPM)	Torque (ft.-lbs.)	Chuck Diameter	Fuel Cap. (fl. oz.)	Dry Weight (lbs.)
EDR-260	25.4	17:1	0-650 forward/reverse	12	1/2 in. standard	19.6	11.4

Model	Engine Disp. (cc)	Carburetor	Max Torque at Engine	Max Torque at Auger	Fuel Cap. (fl. oz.)	Auger RPM	Dry Weight* (lbs.)
EA-410	42.7	Diaphragm w/ Purge Pump	1.62 ft.-lbs. (2.2 Nm)	48.97 ft.-lbs. (66.4 Nm)	33.8	348	21.6

Model	Engine Disp. (cc)	Carburetor	Fuel Cap. (fl. oz.)	Dry Weight (lbs.)
TC-210	21.2	Diaphragm w/ Purge Pump	16.9	21.3

Extension Shafts

ECHO extension shafts are compatible with 3 in. - 10 in. diameter earth augers. Not for use with 12 in. diameter or larger earth augers.

Diameter (in.)	Length (in.)	Part #
7/8	12	99944900220
7/8	18	99944900210

Earth Auger Adapter with Spring	Part #
Converts 7/8 in. to 1 in. diameter	99944900335

Earth Auger Blades & Points

Description	Part #
4 inch auger	99944900230
6 inch auger	99944900240
8 inch auger	99944900250
10 inch auger	99944900260
Auger Replacement Point	99944900270

Ice Auger Replacement Blades & Points

Description	Part #
Replacement blade for 8 in. auger	99944900300
Replacement blade for 10 in. auger	99944900310
Ice Auger Point	99944900275



ENGINE DRILL ACCESSORIES

Description	Part #
2.5 in. dia. Bulb/Plant Auger (24 in. L)	99944900011
3 in. dia. Bulb/Plant Auger (24 in. L)	99944900021
3 in. dia. Heavy-duty Auger (18 in. L)	99944900061
7 in. dia. Gallon Pot Auger (12 in. L)	99944900070
Keyless Chuck	99944900320

